

PVC SEAM SEALER



alkor**PLUS**[®] 81038
BY RENOLIT WATERPROOFING

RENOLIT WATERPROOFING
EXCELLENCE IN ROOFING



PVC SEAM SEALER

SOLUTION OF FLEXIBLE POLYVINYL CHLORIDE (PVC-P) IN TETRAHYDROFURANE (THF)

PRODUCT DATA

Appearance	Volatile, mobile liquid		
Odour	ethereal		
Consistency	Viscous, 0.5 mPa.s at 20°C		
Flash point	-21°		
Boiling point/range	65-66°C		
Flammability (solid/gas)	Upper explosion limit: 12 %(V) Lower explosion limit: 1.5 %(V)		
colours	60884 (copper green)	82119 (terracotta)	71004 (light grey)
	79851 (charcoal)	62945 (green)	73321 (grey)

APPLICATION

- Reinforcement of welded joints, T borders and corners for alkorPLAN[®] waterproofing membranes.
- Shake well before use.
- Dilute only with THF.
- Consumption: approximately 10g/1 lm
- See alkorPLAN[®] installation instructions.

PACKAGING

Type	Colour	Packaging	Content	Unit
81038010	60884	1L	Can	6
81038011	82119	1L	Can	6
81038004	71004	1L	Can	6
81038006	79851	1L	Can	6
81038008	62945	1L	Can	6
81038024	73321	1L	Can	6

STORAGE

- Store in dry unheated places, in original packaging. Protect from sun and frost.
- Ventilate well during and after application.
- Regulations concerning flammable liquids must be observed.
- Do not empty into drains. Take precautionary measures against static discharges.
- Refer to the text on the label and take into consideration the data given on the material safety data sheet, which is available on request.

TRANSPORT

Proper shipping name: ETHER, N.O.S. (MIXTURE, CONTAINS TETRAHYDROFURAN)
 IMDG/IATA/ADR : Flammable Liquids ; Class 3 PKg Gr II ; UN Nr 3271

WWW.ALKORPROOF.COM

RENOLIT (UK) Ltd - RENOLIT House, Hammond Road
 Elms Farm Industrial Estate - Bedford MK41 0UD - United Kingdom
 T +44 1234 244230 - F +44 1234 357313 - info@renolit.co.uk

RENOLIT WATERPROOFING EXCELLENCE IN ROOFING

